# **POWER THE FUTURE** OLYMPIA LUBE OIL PROFILE

OLYMPIA LUBE OIL



# COMPANY HISTORY

Olympia Group of Companies started its commercial activities in 1990, when Olympia Lube Oil GmbH was registered in Germany. It was established in UAE in the year 1994. Quality of Olympia lubricants is meticulously checked by the prestigious European Automobile plants in Germany and Sweden. With the high quality approval certificates from these bodies, Olympia products are proud to state that our product ranges are approved by the prestigious Manufacturers like Porsche, Mercedes Benz, BMW, MAN, Volkswagen and Volvo.



# COMPANY HISTORY

The state of the art and the most sophisticated Olympia Plant in the Jebel Ali Free Zone, Dubai has a built up area of over 13,500 sq metres and it has the warehouse of over 3,500 sq metres with the capacity for blending, filling, packing & labelling of different lubricant SKU's. To deliver the highest quality for all Olympia products, the company has an in built modern laboratory with the state of the art equipments and testing techniques which constantly ensures that all Olympia Products meet the highest International Standards.

It also allows our specialists to develop new and tailor made products for our customers with better formulations.

Olympia Oil has the storage capacity of more than 10,000 MT and blending tanks with the production capacity of over 250,000 MT per annum with the modern European equipments and powerful pumps for safety and security of our plant and our staffs, as Safety lies at the heart of our core values.



Further, growth and expansion of our production capabilities and also the product variants are in line with demand of our customers and that gave us a reason to spread our wings across the globe and today our presence is wide across in Russia, Afghanistan, Germany, Ukraine and Kyrgyzstan and also a wide network of Exclusive distributors and agents has been appointed by Olympia in whole of Africa as well as in Australia, Kazakhstan, Turkmenistan, Tajikistan, Pakistan, Bangladesh, Azerbaijan, Iraq, Jordan, Turkey, Kingdom of Saudi Arabia.

Olympia Lube Oil products include high quality motor oils (mineral, semi-synthetic and synthetic lubricants) for Gasoline and Diesel Engines, Transmission Oils, Hydraulic Oils and Greases as well as the speciality

products like Anti Freeze Coolants, Brake Fluids and Industrial & Marine Products. Today, we are a global company with truly International Product range and our goal is to be committed to deliver the best to our customers.





# OLYMPIA LUBE OIL









Besides the manufacturing of our brand, Olympia Oil is also capable of providing private labelling for our customers.

Big numbers of sold German products under the titles of "Olympia" and "Made in Germany", modern packing technology, best designs of cans, highest standards of quality control, laboratory assurance procedures and proper organization of production and packing works formed big interest in joint venture from partners in supply of German oils.





# OLYMPIA LUBE OIL



Therefore, as per the request of our German partners, in 2000, Olympia established a joint venture with Meguin oils of Germany.

Today Olympia lube oil is a big company with huge manufacturing and refilling abilities, big service facilities, wide distribution, branches and customer networks.





The company is able to provide its customers with all types of Automotive and Industrial Lubricants in pack sizes varying from the smallest 0.25 L cans BULK, in flexi tanks of 25000 Liters in 40 feet container. (see our products).





#### THE GROUP HQ IS OLYMPIA LUBE OIL FZCO

P.O. Box 17533, Jebel Ali Free Zone, Dubai, United Arab Emirates Tel.: +971 4 8817334 Fax: +971 4 8817335 Email: oloco@emirates.net.ae ,info@olympiaoil.com Website: www.olympiaoil.com GERMANY, OLYMPIA LUBE OIL GmbH MOSCOW, OOO OLYMPIA OIL KABUL, SHAHAB CO. LTD UKRAINE, OLYMPIA OIL LTD



AREA

# **Olympia Lube Oil** Manufacturing and refilling products.





### OLYMPIA "HI- Tech", Fully Synthetic Engine Oil SAE OW-30

### OLYMPIA Super Tech, Fully Synthetic Engine Oil SAE OW-40



Modern fully synthetic low-viscosity engine oil created for all-year use. The combination of unconventional synthetic base oils with advanced additive technology guarantees a low-viscosity, highly shear-resistant engine oil that is sure to prevent deposit build-up, lower friction loss in the engine and provide optimal wear protection. This leads to savings in fuel consumption whilst at the same time extending the life of the engine. Suitable for petrol and diesel engines, including those with turbo chargers and catalytic converters.



Modern fully synthetic low-viscosity engine oil created for all-year use. The combination of unconventional synthetic base oils with advanced additive technology guarantees a low-viscosity, highly sheer-resistant engine oil that is sure to prevent deposit build-up, lower friction loss in the engine and provide optimal wear protection. This leads to savings in fuel consumption whilst at the same time extending the life of the engine. Suitable for petrol and diesel engines, including those with turbo chargers and catalytic converters.

Performance Levels and approvals:
ACEA A 3-98,
B 3-98
API
Mercedes Benz 229.1,
Volkswagen 502.00/505.00,
Porsche

#### Article Number: 2013.112 Packing sizes:

6X1L, 4X4L, ,60L DRUM, 208L DRUM

A A 3-98,		
98		
SJ/CF		
cedes Benz	229.1,	

Volkswagen 502.00/505.00,

ACE

B 3-

API

Porsche

Performance Levels and approvals:

Article Number: 2084.019 Packing sizes: 6X1L, 4X4L, ,60L DRUM, 208L DRUM



### OLYMPIA Super Partly Synthetic Engine Oil SAE 10W-40

### **OLYMPIA Super Partly Sythetic Diesel Engine Oil SAE 10W-40**



OLYMPIA Super Partly Engine Oil SAE 10W-40 (partly synthetic) is a modern low-viscosity engine oil for all-year use. The combination of synthetic and mineral base oils with advanced additive technology guarantees a low-viscosity engine oil, which lowers friction loss in the engine but provides optimal wear protection. This leads to savings in fuel consumption

whilst at the same time extending the life of the engine. OLYMPIA Super Partly Synthetic Engine Oil SAE 10W-40 (partly synthetic) is particularly recommended for use in petrol engines and fast-running diesel engines, including turbo chargers, and fulfils the latest requirements of all renowned automotive manufacturers.



OLYMPIA Super Partly synthetic Diesel Engine Oil SAE 10W-40 (partly synthetic) is a modern low-friction partly synthetic diesel engine oil for the new generation vehicle. Maximum wear protection properties enable maximum oil change intervals. Idle lubricant for all diesel engines with or without catalytic converter, including a version with turbo chargers. Increase the power of the engine and decrease fuel consumption. Ideal lubricants for diesel engines under extreme operating conditions.

Ensure excellent engine cleanliness and engine emission.Neutralize negative influences from the fuel. Unsurpassed cold weather starting -350C. Increase engine performance and reduce oil consumption. Ensure cleanliness in the engine system and prevents residue deposits.

#### Performance Levels and approvals:

API SL/CF ACEA A3 -98; B3-98 Mercedes-Benz Sheet 229.1 VW 500 00/505 00 (1/97)

#### **Article Number:** 2087.119 **Packing sizes:** 12X1L, 4X4L, 4x5L, 25L,

60L DRUM, 208L DRUM

Performance Levels and approvals: API CF ACEA B3 -98; B4-02 Mercedes-Benz Sheet 229.1 VW 505. 00/501.01

# Article Number: 2087.129

#### **Packing sizes:** 12X1L, 4X4L, 25L, 4x5L, 60L DRUM, 208L DRUM



### OLYMPIA Partly Synthetic Truck - Tech Diesel, Engine Oil, SAE 10W-40



OLYMPIA Partly synthetic Truck-Tech Diesel Engine Oil SAE 10W-40 (partly synthetic) is an Extremely high performance partly synthetic engine oil. Specially designed to exclusively protect modern high performance diesel engines of Heavy-loaded trucks (Off-Roads). Designed using high performance base oils to reach perfect low temp fluidity. high temp viscosity and decreased fuel consumption. These base oils combine with advance additives to allow for the highest protection of all engine parts. Designed to provide maximum change intervals in modern diesel engine. Used in naturally aspirated and turbocharging diesel trucks.

### OLYMPIA Super Diesel Engine Oil SAE 15W-40



A Super Diesel, multi grade Engine Oil, suited as year rounds all purpose oil, especially for economical use in the mixed vehicle fleet. Thanks to its carefully selected additive package, combined with outstanding base oils, it can be used in modern high performance diesel engines, even with extended oil change intervals, as well as in gasoline engines. It satisfies the requirements of leading foreign and domestic manufacturers of diesel and gasoline engines. OLYMPIA is the ideal engine lubricant for gasoline engines with or without catalytic converter, and for diesel engines, including those with exhaust turbo chargers. In case of extended oil change intervals, please observe the directions of the vehicle manufacturers.

#### **Performance Levels and approvals:**

API CI-4 ACEA - E7-04; GLOBAL DHD-1 MERCIDES BENZ, 228.3 MAN M 3275 MTU TYPE 2 VOVO VDS 3 SCANIA LDF-02, MAC EO-M+ CUMMINS - 20077/78 RENAULT TRUCKS, RLD/RLD 2

#### Article Number:

### Packing sizes:

6X1L, 12x1L, , 4X4 L, 4x5L, 20L, 25L, 60L DRUM, 208L DRUM

#### **Performance Levels and approvals:**

ACEA E 2, B 2, A 2 API CF-4/SH MAN 271 Mercedes Benz Sheet 228.3 VW 505.00 Mack EO-K/2 Volvo VDS MTU TYPE 2

#### Article Number:

2037.119

#### Packing sizes:

12x1L, 4x4L, 4x5L, 25L, 60L DRUM, 208L DRUM



### OLYMPIA High Performance Engine Oil SAE 15W-40

### OLYMPIA Premium FAMO, Engine Oil SAE 15W-40



OLYMPIA high performance, multi grade motor oil, suited as year round all purpose oil, especially for economical use in the mixed vehicle fleet. Thanks to its carefully selected additive package, combined with outstanding base oils, it can be used in modern high performance diesel engines. even with extended oil change intervals, as well as in gasoline engines. It satisfies the requirements of leading foreign and domestic manufacturers of diesel and gasoline engines. OLYMPIA High Performance Engine HD-C3 is the ideal engine lubricant for gasoline engines with or without catalytic converter, and for diesel engines, including those with exhaust turbo chargers. In case of extended oil change intervals, please observe the directions of the vehicle manufacturers.



A modern low-friction universal engine oil for use in all engines, under all operating conditions and all environmental stresses (all-vear oil). It's more than fulfils the highest demands that modern diesel and petrol engines currently place on engine oils. Research and testing over the years have resulted in an engine oil with outstanding properties. Advanced additive technology, in association with unconventional base oils. guarantees outstanding low-friction and wear protection properties and enables maximum oil change intervals. The ideal lubricant for all diesel and petrol engines, whether with catalytic converter or not, and including versions with turbo chargers. Can be mixed with all commercially available engine oils.

#### Performance Levels and approvals:

API CF-4/SG, ACEA A2/B2/E2, Allison C-4 Caterpillar TO-2 , Mack T7 MAN 271 Mercedes Benz Blatt 228.1 MIL-L-2104 E MIL-L-46152 D Volvo VDS VWJ 501 01/505 00

#### Article Number:

#### 2065.115 Packing sizes:

12x1L, 4x4L, 4x5L, 25L, 60L DRUM, 208L DRUM

#### **Performance Levels and approvals:**

ACEA A3/B3-04, B4-04 & E 2-96 API SL/CG-4 MAN 271 Mercedes-Benz Sheet 228.1 MACK EO-L Volvo VDS MTU/DDC TYPE 1 Allison C-4 (LEVEL

### Article Number:

2082.129 Packing sizes:

12X1L, 4X4L, 4x5L, 25L, 60L DRUM, 208L DRUM



### OLYMPIA Super Performace Engine Oil SAE 15W-40

### OLYMPIA Performance TOP TRANS, Engine Oil SAE 15W-40



A Engine oil with a high quality level. Proven base oils combined with the reliable additive technology result in an Engine oil, Which as an engine lubricant withstands the loads of gasoline and Diesel engines even under severe operating conditions. It is the ideal lubricant for gasoline engines with and without catalytic converter, and for fast running Diesel engines, including those with exhaust turbo-chargers, which require multi grade oils according to API SF/CD.



OLYMPIA Performance TOP TRANS SHPD Engine oil is a modern low-viscosity universal engine oil use in all engines, under all operating conditions and all environmental stresses (all-year oil). It's more than fulfils the highest demands that modern diesel and petrol engines currently place on engine oils. Research and testing over the years have resulted in engine oil with outstanding properties. Advanced additive technology guarantees outstanding low-viscosity and wear protection properties and enables maximum oil change intervals. The ideal lubricant for all diesel and petrol engines, whether with catalytic converter or not, and including versions with turbo chargers. Can be mixed with all commercially available engine oils.

### **Performance Levels and approvals:**

Article Number:

#### Packing sizes:

12X1L, 24X1L, 4X4L, 60L DRUM, 208L DRUM 4X4L, 4x5L, 25L, 60L DRUM, 208L DRUM

#### **Performance Levels and approvals:**

ACEA -99 E5/B4/B3/A3, ACEA -02 E5/B4/B3/A2 API SL/CI-4, CH-4/ CG-4, CF-4 \Mercedes Benz Blatt 228.3, 229.1 \Volvo VDS III MAN M 3275, MTU Type II VW 505.00/501.01, Global DHD-1, CES 20071 / 20072 / 20076 / 20077 / 20078, Mack EO-M Plus Renault V.I. RLD, John Deere JDQ 78A

#### Article Number:

2040.111

#### Packing sizes:

12X1L, 4X4L, 4x5L, 25L, 60L DRUM, 208L DRUM



### OLYMPIA Super Performace Engine Oil SAE 20W-50

### OLYMPIA Super Extra Premium Engine Oil, SAE 20W-50



High-quality engine oil of the new generation. Time-tested base oils combined with new pioneering additive technology result in an engine oil that withstands all the stresses generated by petrol and diesel engines, even under strenuous conditions. It neutralizes negative influences from the fuel, reduces friction and wear and prevents sludge formation. The ideal lubricant for petrol engines with and without catalytic converters and for fast-running diesel engines, including turbo charged ones



OLYMPIA Super Extra Premium Engine Oil is an engine oil with a high standard of quality. Time-tested base oils combined with pioneering additive technology result in an engine oil that withstands all the stresses generated by modern petrol and diesel engines in all operating conditions. It neutralises negative influences from the fuel, reduces friction and wear and prevents sludge formation.

OLYMPIA Super Extra Premium is an ideal engine lubricant for petrol engines with and without catalytic converters and for fast-running diesel engines including turbo chargers.

#### Performance Levels and approvals: API SF/CD

#### Article Number: 2097.000 Packing sizes:

12X1L, 4x3, 4X4L, 4x5, 20L, 25L, 60L DRUM, 208L DRUM Performance Levels and approvals: API SJ/CF Mercedes -Benz Blatt 229.1 VM 501.01/505.00 MIL-L2 104 E

#### Article Number: 2097.079 Packing sizes:

12X1L, 4x3L, 4X4L, 4x5L, 20L, 25L, 60L DRUM, 208L DRUM



### OLYMPIA Syntech Formula Fully Synthetic Engine Oil, SAE 5W-30



OLYMPIA SynTECH Formula Fully Synthetic Engine Oil especially for the latest generation of gasoline, diesel and gas passengers car and vans. Suitable for engines of all emission classes, especially when equipped with filter system, catalyst or EGR. Reduces engine emission and oil consumption. Excellent engine cleanliness. Suitable for engines with multi-valve technology, valvetronic, and turbo-charging (with or without charge air cooling). Guarantees to provide exceptional protection against wear. Reduces fuel consumption. Ultra high performance oil for euro 4 gasoline and diesel engine service. Increases engine performance and piston cleanliness. Low temperature pumpability and sludge control.

### OLYMPIA Top-Tech Fully Synthetic Engine Oil, SAE 5W - 30



OLYMPIA super low-viscosity engine oil Engine SAE 5W-30 is a modern, fully synthetic low-viscosity engine oil of the new generation for all-year use. The combination of unconventional synthetic base oil components with the latest additive technology guarantees a low-viscosity, highly shear-resistant engine oil that is sure to prevent deposit build-up, lower friction loss in the engine and provide optimal wear protection. This leads to savings in fuel consumption whilst at the same time extending the life of the engine. OLYMPIA super low-viscosity engine oil SAE 5W-30 is recommended for petrol engines and diesel engines including versions with turbo chargers and catalytic converters.

#### **Performance Levels and approvals:**

API SM/CF,ACEA C3-07 (2007), ACEA A3/B4-04 (2007) Mercedes-Benz 229.51 BMW Longlife-04 VM50200, VM50500, VM50501 FORD WSS-M2C 917-A

#### Article Number:

2096.119

#### Packing sizes:

12X1L, 4X4L, 4x5L, 60L DRUM, 208L DRUM Performance Levels and approvals: ACEA A5/B5-08 API SL/CF MERCEDES BENZ 229.1 VW 502.00 / 505.00 Renault 700 
 Article Number:

 2096.119

 Packing sizes:

 12X1L, 4X4L, 4x5L,

 60L DRUM, 208L DRUM



### OLYMPIA Pro-Tech Fully Synthetic Engine Oil, SAE 5W - 40

### OLYMPIA HI-RACE Fully Synthetic Engine Oil, SAE 5W-50



This is a modern fully synthetic low-viscosity engine oil for all-year use. The combination of unconventional synthetic base oil components with the latest additive technology guarantees a low-viscosity, highly shear-resistant engine oil. that is sure to excellent fuel economy . Reduces oil consumption. Unsurpassed cold weather -450C starting excellent protection in high temperature. Increased engine performance and excellent engine cleanliness. Reduces engine emissions. Far superior to semi synthetic & mineral oil. High shear / high temperature viscosity. For all petrol & diesel engines. With or without turbo or catalytic converter.



This is a modern fully synthetic low-viscosity engine oil for all-year use. The combination of unconventional synthetic base oil components with the latest additive technology guarantees a low-viscosity, highly shear-resistant engine oil. that is sure to excellent fuel economy . Reduces oil consumption. Unsurpassed cold weather -450C starting excellent protection in high temperature. Increased engine performance and excellent engine cleanliness. Reduces engine emissions. Far superior to semi synthetic & mineral oil. High shear / high temperature viscosity. For all petrol & diesel engines. With or without turbo or catalytic converter.

#### Performance Levels and approvals:

ACEA A3-98/B4-98, API SM/CF Mercedes Benz 229.3 PORSCHE VW 502.00 / 505.00 BMW LONG LIFE 98

#### Article Number: 2081.119 Packing sizes:

6X1L, 4X4L, 4x5L, 60L DRUM, 208L DRUM Performance Levels and approvals: API SL/CF

ACEA A3/B3

Article Number: 2080.009 Packing sizes: 6x1L, 4x4L, 4x5L, 60L, 208L DBUM



### OLYMPIA Super Diesel Engine Oil, SAE 50

### OLYMPIA Hypoid Super Gear Oil, SAE 80W-90 GL-5



This single-grade engine oil with a naturally high viscosity index is made from a basis of extremely ageing-resistant solvent reagents together with optimally selected active agents. Their specific properties make them ideal for use in turbocharged diesel engines and four diesel engines in extreme operating conditions. Their high alkaline reserve prevents corrosion even when diesel fuel with a high sulphur content is used.



This Multi grade gear oil with advanced additive technology. Unique low friction properties. Extended equipment life. Total drive line capability. Gear oil with agents for reducing wear on bearing & tooth faces. Special additives prevent rust and foam formation. Suitable for a wide range of application. Excellent viscosity temperature behaviour.

Outstanding resistance to ageing & cold. For use in heavy load motor vehicle transmission, particularly axle driven with hypoid gearing.

#### Performance Levels and approvals:

API CF/CD/SF, ACEA E1-96 Caterpillar TO-2 ALLISON C3 Mercedes Benz Blatt 227 MIL-L-2104 D

#### Article Number: 2075.111 Packing sizes: 6x1L, 12X1L, 4x3L, 4X4L, 4x5L, 20L,

25L, 60L DRUM, 208L DRUM

Performance Levels and approvals: API GL-5 MAN 342N ZF TE ML 05A, 07A,12E, 16B, C, D, 17B, 19B MERCEDES BENZ 235.0 Article Number: 2129.119 Packing sizes: 12X1L, 60L DRUM, 208L DRUM



### OLYMPIA High Tech Gear Oil, SAE 80W-90 GL-4

### OLYMPIA Anti Freeze OAF 7000, G-11



These are high performance multi purpose gear oil. Reduces temperature & minimize running noise. Extended drain capability. Proven reduction in operating temperatures. Universal use in all types of transmission: Super gear, Bevel gear, worm gear. Extended life & reducing wear on bearing and teeth. Optimum lubrication at low & high temperature. Selected base oil & Special additives provides high pressure gear oils.



OAF 7000 G-11 antifreeze is suitable for all cooling systems, especially for aluminium engines. Protects engine from freezing, rusting and over heating. Free of nitrates, amines, phosphates and silicates. Antifreeze and corrosion inhibitor. Used in car and truck engines as a nitrate and silicate -free radiator antifreeze. Best diluted with deionized or drinking water. Contains effective Anti-corrosion inhibitors to protect the metals of the engine block and the radiator. Prevents line deposits from water and the swelling of coolant hoses and seal. 1Ltr Olympia antifreeze OAF 7000 = - 800C

#### **Performance Levels and approvals:**

API GL-4 MAN 341 ZF 02A, 17A MERCEDES BENZ 235.1

# Article Number: 2116.111

Packing sizes: 12X1L, 60L DRUM, 208L DRUM Performance Levels and approvals: MERCEDES BENZ 325.3 PORSCHE, VW, SEAT, SKODA & AUDI TL 774D, NISSAN, MAN 324, MTU MTL 5048, BMW, RENAULT, GM VOLVO, TOYOTO Article Number: 36700111 Packing sizes: 12X1L, 4x4L, 60L DRUM, 200L DRUM



### OLYMPIA Anti Freeze OAF 7100, G-12

### OLYMPIA Anti Freeze OAF 7200, G-13



OAF 7100 G-12 antifreeze is suitable for all cooling systems, especially for aluminium engines. Protects engine from freezing, rusting and over heating. Free of nitrates, amines, phosphates and silicates. Antifreeze and corrosion inhibitor. Used in car and truck engines as a nitrate and silicate -free radiator antifreeze. Best diluted with deionized or drinking water. Contains effective Anti-corrosion inhibitors to protect the metals of the engine block and the radiator. Prevents line deposits from water and the swelling of coolant hoses and seal. 1 Ltr Olympia antifreeze OAF 7100 = - 800C



OAF 7200 G-13 antifreeze is suitable for all cooling systems especially for aluminium engines. Protects engine from freezing, rusting and over heating. Free of nitrates, amines, phosphates and silicates. Antifreeze and corrosion inhibitor. Used in car and truck engines as a nitrate and silicate -free radiator antifreeze. Best diluted with deionised or drinking water. Contains effective Anti-corrosion inhibitors to protect the metals of the engine block and the radiator. Prevents line deposits from water and the swelling of coolant hoses and seal. 1 Litre Olympia antifreeze OAF 7200 = - 800C

#### **Performance Levels and approvals:**

MERCEDES BENZ 325.3 PORSCHE, VW, SEAT, SKODA & AUDI TL 774D, NISSAN, MAN 324, MTU MTL 5048, BMW, RENAULT, GM VOLVO, TOYOTO

#### Article Number: 36710111 Packing sizes: 12X1L 4x4L 60L DRUM.

200L DRUM

#### **Performance Levels and approvals:**

MERCEDES BENZ 325.3, PORSCHE, VW, SEAT, SKODA & AUDI TL 774D, NISSAN, MAN 324, MTU MTL 5048 BMW, RENAULT, GM VOLVO, TOYOTO 
 Article Number:

 36711111

 Packing sizes:

 12X1L, 4X4L, 60L DRUM,

2001 DRUM



### OLYMPIA Automatic Transmission Fluid, Dexron III

OLYMPIA ATF D III is a hydraulic fluid for automatic transmission and hydraulic clutches, which require an automatic transmission fluid type Dexron III. Assures faultless functioning of the hydraulic transmission even under the most severe operating conditions and great temperature changes. May also be used as a hydraulic fluid for systems working under extreme operating condition.

### OLYMPIA Automatic Transmission Fluid, Dexron II D



OLYMPIA ATF II D is a hydraulic fluid for automatic transmission and hydraulic clutches, which require an automatic transmission fluid type Dexron II. Assures faultless functioning of the hydraulic transmission even under the most severe operating conditions and great temperature changes. May also be used as a hydraulic fluid for systems working under extreme operating condition.

#### **Performance Levels and approvals:**

VOITH G 607 ZF TE-ML 04D, 17C ALLISON C4, CATERPILLAR TO-2, FORD MERCON, GM DEXRON II E, GM DEXRON III, MAN 339-C, MERCEDES – BENZ BLATT 236.1, OPEL

#### Article Number: 2268.111 Packing sizes:

12X1L, 4X4L, 60L DRUM, 208L DRUM

#### Performance Levels and approvals:

VOITH G 607 ZF TE-ML 04D, 17C ALLISON C4, CATERPILLAR TO-2, FORD MERCON, GM DEXRON II E, GM DEXRON III, MAN 339-C, MERCEDES – BENZ BLATT 236.1, OPEL

#### Article Number:

2266.11

#### Packing sizes:

12X1L,4X4L, 60L DRUM, 208L DRUM



### OLYMPIA Super Hydraulic HLP 32

### OLYMPIA Super Hydraulic HLP 46



OLYMPIA SUPER HYDRAULIC HLP-32 is increased ageing resistance, anti corrosive properties. Extreme pressure properties. Satisfy all requirements & anti-wear hydraulic properties.



OLYMPIA SUPER HYDRAULIC HLP-46 is increased ageing resistance, anti corrosive properties. Extreme pressure properties. Satisfy all requirements & have anti-wear hydraulic properties.

### Performance Levels and approvals:

DIN 51524 - HLP 32 (part 2) AFNOR NF E 48-603 HM CINCINNATI MILACRON P-70 Article Number: 2203.111 Packing sizes: 25L, 60L DRUM, 208L DRUM Performance Levels and approvals: DIN 51524 - HLP 46 (part 2) AFNOR NF E 48-603 HM CINCINNATI MILACRON P-70 Article Number: 2204.111 Packing sizes: 25L, 60L DRUM, 208L DRUM



### OLYMPIA Super Hydraulic HLP 68

### OLYMPIA Multi Purpose Grease K2K-30, MP2



OLYMPIA SUPER HYDRAULIC HLP-68 is increased ageing resistance, anti corrosive properties. Extreme pressure properties. Satisfy all requirements & have anti-wear hydraulic properties.



OLYMPIA SUPER MP GREASE IS A PREMI-UM GRADE, LITHIUM BASED MULTI PURPOSE GREASE. It is given Good water resistance, Good mechanical and oxidation stability & excellent resistance to rust. Then suitable for all automotive, agricultural and industrial application.

#### **Performance Levels and approvals:** DIN 51524 - HLP 68 (part 2)

AFNOR NF E 48-603 HM CINCINNATI MILACRON P-70

### Article Number: 2206.111 Packing sizes:

25L, 60L DRUM, 208L DRUM

**Performance Levels and approvals:** NI GLMP-2 Article Number: 2206.111 Packing sizes: 500gm, 18Kg



### OLYMPIA Brake Fluid, DOT 3



Speller and grammar checker English OLYMPIA BRAKE FLUID is a high quality, non evaporating, non-freezing brake fluid for use in all seasons and for all types of cans, trucks and buses. This brake fluid doesn't only correspond to SAE specification 70R 3 and J1703 but even surpasses the requirements in many points. It confirms in its physical and chemical properties to the US safety standard FMVSS 571.116/DOT 3.

### OLYMPIA 2T Super out Board



OLYMPIA 2T SUPER OUT BOARD is the latest generation of two-stroke engine lubricant for high performance outboard engines. It has been formulated with special base stocks that provide a low ash lubricant to help support the protection of lakes and oceans. OLYMPIA 2T SUPER OUT BOARD exceeds the latest NMMA TC W3 certified oil specification requirements for high performance two-stroke engines.

- **D** Reduced engine deposits
- Improved environmental exhaust pollution protection
- Reduced engine wear
- Minimized tendency for pre-ignition
- Long engine service life

**Performance Levels and approvals:** 

Article Number: 2206.111 Packing sizes: 250ml. 500ml **Performance Levels and approvals:** NMMA TC-W, TC-W II, TC-W3

Article Number: 2206.112 Packing sizes: 250ml 500ml 11 tr



### OLYMPIA 2T Super Plus



OLYMPIA 2T SUPER PLUS is a high quality two-stroke engine oil that has been developed for small to medium size air cooled two-stroke engines used in motorcycles, scooters and snow bikes. Formulated with a modern low ash additive system which offers protection against scuffing of piston rings and liner wear by minimising piston ring deposits.

- **D** Reduced engine deposits
- Reduced engine wear
- Reduced tendency for pre-ignition
- Long engine service life

### OLYMPIA Ultra Brake Fluid, DOT 4



OLYMPIA BRAKE FLUID is a high quality, non evaporating, non-freezing brake fluid for use in all seasons and for all types of cans, trucks and buses. This brake fluid doesn't only correspond to SAE specification 70R 3 and J1703 but even surpasses the requirements in many points.

It confirms in its physical and chemical properties to the US safety standard FMVSS 571.116/DOT 4

#### Performance Levels and approvals:

JASO : FB, API : TB

Article Number: 2206 113 Packing sizes: 250 ml, 500ml, 1 Ltr **Performance Levels and approvals:** DOT 4

**Article Number:** 2206 114 **Packing sizes:** 250ml, 500ml



# OLYMPIA LUBE OIL CERTIFICATES

Besides, from globally recognized automotive manufacturing companies. Olympia products received quality approvals for high performance cars from worldwide famous car manufacturing companies, such as Mercedes Benz, Volkswagen, Volvo, Renault and MAN.

DAIMLER	DAIMLER	DAIMLER	DAIMLER WINN
Nacional per la Coloma En de Secondo Se Casto Francía da Coloma Secondo Secondo Secondo Secondo Secondo Secondo Secondo Secondo Secondo Secondo Secondo Secondo Secondo	Remark Law Science with the Science Hellin Science Transmitter Allower Science Science Science Allower Science	manewa Judio Gili Soute wan, dan searang Manewa Lynan Roman Kit attitute Kurat Kali Laki. Romanikan	Haran - M Henrowyki Brinneski, dan 50 (1000) Brinneski (1000) Brinneski (1000) Brinneski (1000) Brinneski (1000) Brinneski (1000) Brinneski (1000)
and the second	2007 (Pr)+ 400	Service and Arts	100 Con 100 Co
EALERS INVESTIGATE University - 22.00	WEAT AND ALL ALL ALL ALL ALL ALL ALL ALL ALL AL	Success diamond when we we	No. 2017 Sectors Secto
MB-Approval Certification	Mb Approval Complicate	NID-Approval Certificate	IIIS Appreciat Certificate tea county - transity
Alt Approval fun Tappine Dir Yozh Miller 7 Sagari Family Bywtenin? Weiter - Beit Herrin Bornson (Schlader 1998) (Beit Der Herrin Beiter Beiter - Beiter Herrin Schlader (Schlader 1998) (Beit Der Herrin Beiter Beiter - Beiter F	MEApproval for Impire 20 "CLYMPA 7 to 1101 FORMULE PLACE WITHOUT - Topola 4 (2022) 12 (CLYMPA 2004) Interview, 2023 (CLYMPA 2004) INTERVIEW, 2024 CLAR 20 Interview, 2024 (CLYMPA 2004) INTERVIEW, 2024 CLAR 20 Interview, 2024	Hill Argument Ann Thaghan Car Yozy DER S Y Face Scale Failing Dynamics? Materials in the contract of colours of an annual scale of the colour s	Hill Against 2023 Soc "SCHMM / HOPORIMAGE TOP TANKE SIN AC" OF Code -, SAR Guides 100:40 mission in control and mission for last end of comparison (3.4). San Str. A Schman, San Schman, Str. A Schman, Sch
ne is street,	The R & Table	Date St. of Myslers,	For proceedings) providing that constrain with the maximum later the decision of the decision from the later the second s
To generate the generate shows memory and the registrements of the foreign the destination for personal fragments (registre and the state and the state of the foreign state of the state of the memory in the angulation straps of the state and the state of the state of the L. For state statements, get of generate strands and the state and the state of the s	The sensing find of part does infplant give a supervised of the Research direct Sector Ver- Standing Frank, Amer 1994 give a Research associated to all or the reference where we need to channel of Frank, and the Frank give a supervised of the Sector Version and the Sector Version of the Sector Version and Sector Version and Sector Version and Sector Version 1990 groups a value and sector large of the sectors. Sec webby particular instance of the sector particular 1990 groups a value and sector large of the sectors.	The section will be also associated with the implementary time inter-stock over intermeted and proving sizes, many effects of the interface and will be also be also been associated and concerning. The exploration range or items and weathers to the section 2011. The stree restrements, e.g. Long previous systemics, recently and most interface and interview. This approval is splanish the section of the end that an end previous address of the section previous of the training previous systemic and the section of the section previous address in the section previous of the training previous systemic and the section of the section previous address in the section previous of the section previous systemic and the section of the section previous address of the section previous of the section previous systemic and the section of the section previous address of the section previous of the section of the section previous address of the section previous of the section previous of the section of the section previous address of the section previous of the section previous of the section previous of the section previous address of the section previous of the section previous of the section previous of the section previous address of the section previous of the section previous of the section previous of the section previous address of the section previous o	<ul> <li>An advanced set of a strate instantistic interpret memory and in the determined of the strategies of the st</li></ul>
Alone in provide a provide set of a set of the set of t	Hand in the second original and parts and the second in the second free second free second and the based of the good the (1) the second of parts (and the second parts) and and any second second the second of all them, and the the second second community of the parts (second parts). The second second second second	Versupports is statisfied that of the ordinates. The statist parties activities to be stating and of the device extension ingrise probability of the statistical statistical statistical tests in the statistic parties for a generative. A 1 the statistical statistical statistical statistical statistical statistical statistical statistical and the statistical statistical statistical statistical statistical statistical statistical statistical statistical and the statistical st	<ul> <li>The set integrated is one and in tag as the above have a branch with the (MV) of http://www.setainteendorum.</li> <li>Mechanism &amp; Annual is also applied to setaintee a process in addition, for equivalence to the second "Obligation Engineering Agence to the Figure 's and year.</li> </ul>
an an ann gun a gun an an an an gun ann ann ann ann ann ann ann ann ann a	too too ay an a canada a a ay gar anana. A ana ana ana ana ana ana ana ana ana a	In the second seco	Figure 1 sectors in starts 4.3 Per lambing and and figure (New all block and as in a start of general factors AB all any general word in anomaly for and figure (New all block appendix) and the starts.
sil- vehalt	w V/ TT-A-St	Cil- 11 And	Minimu Annual Al
a factore and a second second second	an me	an and the second secon	18 3 and 10 million
Manufacture Manuf		In the second se	Restrict to 0 classes (Classes)     Restrict (Classes)     Restrict (Classes)     Restrict (Classes)     Restrict (Restrict (Restrit (Restrict (Restrict (Restric
VOLVO		VOLKSWAGEN	
Provention Dr./1997-14.1289 Str. Doctor	MAR REPORTED OVER		
Do, Marine Laboration, Sanchar (Cristical enformation and Cristical enformation and Cristical enforcements and a sector interconstruct A and a clistower?		And and a second	Managerine: System as per EM ISO 3851 : 2008
Di Vinge Lanta de Lanta (1710 e la marca de 2010 e la marca de 2010 e la marca de 2010 e la marca 2010 e la marca de 2010 e la marca Agresa de 2010 e la marca de 2010 e la marca Agresa de 2010 e la marca de 2010 e la marca de 2010 e la marca Agresa de 2010 e la marca de 2010 e la marca de 2010 e l	Charles (K. 1994) Charles (K. 1994) Statistical Statistics Stat	Normal and the second s	Managemers system as par
extense and extense (respectively) for a second of the formation of the formation of the second of t	A Constant of the second secon	August and the second s	Managerine: System as per EM ISO 3851 : 2008
Overthis safet as, provin Vertical and a second se	A service of a ser	An and a second	EN (SC 8161 - 2008 Anatomic Science Density attracts
Overthal Later dr. Ensem Later of Angel Barris and Angel Manager a	A service of a ser		
Overthis safet as, provin Vertical and a second se	A service of a ser		
<text><text><text><text><text><text></text></text></text></text></text></text>			<text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text>
<text><text><text><text><text><text><text></text></text></text></text></text></text></text>			<text></text>
<text><text><text><text><text><text><text></text></text></text></text></text></text></text>		<text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text>	<text><text><image/><section-header><section-header><text><text><text><text><text></text></text></text></text></text></section-header></section-header></text></text>
<text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text>		<text><text><text><text><text><text></text></text></text></text></text></text>	<text></text>





## QUALITY CONTROL



It allows companies to carry out very complicated tests and to avoid any complaints in quality, quantity, packing and delivery of lubricants. All suppliers of Olympia are strongly complying with the demands of Olympia QC. All Olympia products are protected against any kind of duplication and calcification.

Olympia is always supplying high quality products in best packing and safe containers.

Olympia has established a sound and robust quality control system during receipt of raw materials, in processing lubricants, refilling, final packaging and delivery of the finished products. The quality control is carried out by highly qualified and trained technicians. Olympia owns best laboratory equipment for lab quality assurance, unique testing apparatus and strong QC procedures.



## OLYMPIA SERVICES



Olympia is dedicated to provide its customers additional following benefits and services beside the production, refilling and delivery of high quality lubricants:

- Oil branding
- Lubrication surveys
- Research and development Service
- Oil Quality Monitoring program
- **D** Laboratory quality assurance facilities
- Description Motor oil blinding,
- Automatic transmission fluid blinding
- Anti freeze blinding
- Refilling services
- Advise Instruction and training in the use and main tenance of Lubricating and related equipment.
- **D** Package development and services for specific customer needs

# OLYMPIA LUBE OIL



Ahmad Shah Shahab Chairman – Olympia Lube Oil FZE.



Olympia Lube Oil was purely established with the aim of responding to our customers needs in an efficient, dynamic and profitable way and guide our esteemed customers with our comprehensive product range. We are committed to continuously evolving & updating our product quality and range to ensure that the Olympia products are manufactured with the most advanced formulations.

We are fully committed to maintain the highest quality in everything we do and you can be rest assured that you are dealing with a company that is striving to achieve total customer satisfaction

Our complete range of products will enhance your vehicle performance and experience. Our team of experts, be it in quality or sales are always available to guide you with the right solution.

Finally, you can trust us with confidence that our team is always at your service to meet your requirements at short notices to guarantee your uninterrupted working goals.

"Together, we will achieve success" is our goal and our motto.

# DISTRIBUTORS



### Countries

Afghanistan Lebanon Australia Mali Bahrain Nigeria Bangladesh Pakistan Benin Qatar Burkina Faso Russia Tajikistan Egypt Germany Togo Turkmenistan Iraq Ivory Coast Ukraine Kazakhstan Uzbekistan Kyrgyzstan U.A.E Kingdom of Saudi Arabia United Kingdom





### **GET IN TOUCH**

#### THE GROUP HQ IS OLYMPIA LUBE OIL FZCO

 P.O. Box 17533, Jebel Ali Free Zone, Dubai, United Arab Emirates

- **\$** +971 4 8817334
- +971 4 8817335
- (a) oloco@emirates.net.ae / info@olympiaoil.com



www.olympiaoil.com